SECTION II NM 17/04

NAVIGATION PUBLICATIONS

FLEET GUIDES CORRECTIONS

PUB 941 4 Ed 2004 NEW EDITION (NGA) 17/04

SAILING DIRECTIONS CORRECTIONS

PUB 172 9 Ed 2001 LAST NM 14/04

Page 208—Line 25/R; read:

alongside depths of 2.7 to 4m. General cargo vessels, with a maximum length of 80m, can be accommodated. All container or ro-ro cargo is handled at the facilities in Mina Khalid.

(PUBS 001-04) 17/04

PUB 173 7 Ed 2002 LAST NM 16/04

Page 92—Lines 20 to 23/R; read:

Oiling Berth No. 1 lies about 0.2 mile W of Round Point and can accommodate vessels up to 200m in length with a draft of 9.7m.

Prima Jetty, a T-headed jetty, is situated SW of Round Point. It is flanked by dolphins and can accommodate vessels up to 230m in length and 70,000 dwt. There is an alongside depth of 13m.

(BA NP 38) 17/04

Page 128—Line 53/R; insert after:

A submarine cable and pipeline area has been established between the Godavari River entrance and False Divi Point. The limits of this area, known as the Ravva Oilfield Development Area, may best be seen on the chart. Anchoring and fishing are prohibited.

(BA NP 21) 17/04

COAST PILOT CORRECTIONS

COAST PILOT 5 31 Ed 2004 Change No. 16 LAST NM 15/04

Page 378—Paragraph 61, lines 6 to 7; read:

Island Channel to the mouth of Dog River. In January 2004, the controlling depth was 6.7 feet (7.0 feet at ...

(CL 305/04) 17/04

Page 393—Paragraph 257, line 9; read:

2004, 6.2 feet (11.0 feet at midchannel) to the seaway. (CL 302/04) 17/04

Page 394—Paragraph 269, lines 10 to 13; read:

vicinity of Three Rivers Road. In January 2004, the controlling depth was 9.9 feet (11.4 feet at midchannel) to Light 5, thence 2.6 feet (12.0 feet at midchannel) to Light 11, thence 10.2 feet (11.0 feet at midchannel) to the ...

(CL 303/04) 17/04

Page 446—Paragraph 20, lines 13 to 14; read:

marked by lights off the ends of the jetties and a lighted bell buoy about 1.7 miles S of the jetties. The channel is not well defined due to erosion and local knowledge is advised.

(CL 181/04; LL/03)

17/04

COAST PILOT 8 25 Ed 2003 Change No. 18 LAST NM 10/04

Page 148—Paragraph 302, line 6; read: (55°23'41"N., 131°45'53"W.), 24 feet (7.3 m) above the ... (03/04 CG17; LL/03) 17/04

Page 150—Paragraph 321, line 3; read:

bight in the W shore about 1 mile N of the S tip of **Sharp Point** ...

(NOS/04) 17/04

Page 165—Paragraph 130, lines 3 to 4; read: side. **Tamgas Harbor Entrance Light** (55°01'19"N., 131°30'49"W.), 30 feet (9.1 m) above the water, is shown ... (03/04 CG17; LL/03)

Page 230—Paragraph 523, lines 18 to 20; read:

the dredged sections of the channel. In May 2000, the controlling depth was 8.9 feet in the dredged sections of the channel with 3.7 feet in the right outside quarter at Daybeacon 9 and 7.1 feet in the left outside quarter between Daybeacon 3 and Daybeacon 2.

(BPs 171981-996) 17/04

Page 244—Paragraph 146, line 4; read: the latter. A lighted buoy is about 0.2 mile N of the ... (06/04 CG17) 17/04

Page 275—Paragraph 106, line 1; read:

Grave Point Light (58°03'44"N., 134°03'04"W.), 45 ... (LL/03) 17/04